Dimplex Fireplace Insert Manual



File Name: Dimplex Fireplace Insert Manual.pdf

Size: 4392 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 14 May 2019, 17:24 PM

Rating: 4.6/5 from 572 votes.

Status: AVAILABLE

Last checked: 1 Minutes ago!

In order to read or download Dimplex Fireplace Insert Manual ebook, you need to create a FREE account.

Download Now!

eBook includes PDF, ePub and Kindle version

- Register a free 1 month Trial Account.
- ☐ Download as many books as you like (Personal use)
- ☐ Cancel the membership at any time if not satisfied.
- **☐ Join Over 80000 Happy Readers**

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dimplex Fireplace Insert Manual . To get started finding Dimplex Fireplace Insert Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Dimplex Fireplace Insert Manual

Select the appropriate document type from the drop down menu once selected, the document file will appear below, allowing you to download it for use. If you have misplaced the manuals supplied with your product, please enter the product model number into the search bar below, choose your product and then select the Manuals and Guides tab to download a copy of them. Electric Fireplace Manual Control The manual controls for the unit are located in the top, right corner, on the front of the firebox Figure 1. Page 4 The remote control has a range of approximately 50 feet 15.25 m. It does not have to be pointed at the fireplace and can pass through most obstacles including walls. It is supplied with one of 243 independent frequencies to prevent interference with other units and the frequency designation is indicated on the back of the remote control. Replace battery when needed with a 9 volt battery. Log set Disconnect power before attempting any maintenance or cleaning to reduce the risk of electric shock or damage to persons. Replacement Procedure 1. Page 12 within the firebox. Be sure to note each wire's original location carefully. Figure 7.5. Remove the switch by depressing the retaining clips Figure 6 and pushing the switch forward, through the sheet metal of the firebox. NOTE Due to the switches' placement under the lip of sheet metal, it may be necessary to use a large flatheaded screwdriver to slide between the switch and sheet metal in order to depress the top retaining clip. Page 13 Power Cord Replacement ii Remove the two 2 piggyback and three 3 single wire connectors from the heater element and motor, noting their original locations. If the firebox was operating prior to servicing allow at least five 5 minutes for light bulbs and heating element to cool off to avoid accidental burning of skin. Flicker Rod Bulbs 2 Light bulbs need to be replaced when you notice a dark section of the

flame.http://yeagersadc.com/files/cadillac-escalade-2002-owners-manual.xml

• dimplex fireplace insert manual, dimplex electric fireplace insert manual, dimplex fireplace insert manual, dimplex fireplace insert manual, dimplex fireplace insert manual, dimplex fireplace insert user manual.

There are two 2 bulbs under the log set which generate the flames and embers. Disconnect power before attempting any maintenance or cleaning to reduce the risk of electric shock or damage to persons. Page 15 2. Carefully remove the Log Set from the firebox. Figure 14 3. Disconnect LED harness to Log Set DFI2310 only. Set Log Set aside Figure 12. Terminal Block Cover Capacitor Flicker Motor 4. Pull Flicker Rod to the far right, towards the Flicker Motor, carefully bend the Flicker Rod enough to release the opposite end from the mounting bracket Figure 12. Remote Receiver Board Disconnect power before attempting any maintenance or cleaning to reduce the risk of electric shock or damage to persons. Page 18 13. Remove the two 2 Phillips light socket screws from the rear of the light assembly Figure 19. Page 19 Figure 21 Log Driver Board back panel and just under the terminal block Figure 21. 7. Either pinch the clasp to release or cut each of the four 4 mounting studs one in each corner of the Log Driver Board that attach the circuit board to the chassis of the firebox. ! NOTE If mounting studs are cut, ensure they are replaced by those supplied with replacement board. 8. Clear both ends of mounting studs if cut. 9. Page 20 Troubleshooting Guide PROBLEM CAUSE SOLUTION General Circuit breaker trips or fuse blows when unit is turned on Short in unit wiring. Trace wiring in unit. Improper circuit current rating Additional appliances may exceed the current rating of the circuit breaker or fuse. Plug unit into another outlet or install unit on a dedicated 15 amp circuit. Unit turns on or off by itself Remote Control has a similar frequency to other remotes in the area. Replace Remote

 $Control. \underline{http://www3.grupoct.com.br/dev/grupo_ct/arquivos/cadillac-escalade-manual-2006.xml}$

Page 21 PROBLEM CAUSE SOLUTION Heater Heater is not turning off Heater is not turning on, but flame effect is still functioning Heater is turning off after a couple of minutes of operation Heater emits an odor Heater fan turns on but heater lacks heat Heating element is glowing red Improper operation Refer to Operation Section Defective Heater Switches Replace Heater Switches Improper operation Refer to Operation Section Loose wiring Trace wiring in unit. For your safety, always comply with all warnings and safety instructions contained in this manual to prevent personal injury or property damage. Next Page 2 Table of Contents. Thank you and congratulations for choosing to purchase an electricPage 4 Important Instructions Important InstructionsIf you must use an extensionPage 6 Important InstructionsPage 7 Fireplace Installation Fireplace Installation. Unpacking Instructions Figure 2. The fireplace insert is packed with Page 9 Fireplace InstallationPage 10 Fireplace InstallationPage 11 Operation Operation. To access the controls, swing position the heater operates if the Page 12 Operation Page 13 Maintenance Operation Page 15 Warranty WarrantyOne Year Limited Warranty material and workmanship for a period. Page 16 WarrantyPage 17 Replacement Parts Replacement Parts. Model. Page 2 QUICK REFERENCE GUIDE FOR THE DIMPLEX ELECTRICPage 3 IMPORTANT INSTRUCTIONSPage 4 IMPORTANT INSTRUCTIONSA 15amp, 120 volt circuit is required. A dedicated circuit is preferred but not essential in allClearance for air circulation beneath the fireplace insert is provided by three rubber feet. Should the heater overheat, an automatic switch will turn the heater off and it will. Page 9 FREQUENCY INTERFERENCE. If the fireplace does not respond properly to the remote control, the remote operatingPage 12 To access the lower light bulb areaThe filter should beProducts to which this limited warranty applies. This limited warranty applies to the following model of.

Page 15 What this limited warranty does not cover. This limited warranty does not apply to products that have been repaired except. Page 16 For surrounds mantels and trims for the period ending at midnight on the first. Please check your inbox, and if you can't find it, check your spam folder to make sure it didnt end up there. Please also check your spam folder. Thank you for allowing our product to be the backdrop for those special moments. Also check the 2 light bulbs at the top of your firebox. This odor is a normal condition caused by the initial heating of internal heater parts and will not occur again. If this does not work, switch the unit off for 5 minutes and try again. Consult page 5 of your Practical Users Guide for further information. To avoid burns, do not let bare skin touch hot surfaces. The trim around the heater outlet becomes hot during heater operation. Keep combustible materials, such as furniture, pillows, bedding, papers, clothes, and curtains at least 3 feet 0.9m from the front of the unit with the exception of BF4000NT model which has zero clearance requirements, however, it is recommended to leave 5 inches 13cm of clearance in front of the grill so that it may open. Return heater to authorized service facility for examination, electrical or mechanical adjustment, or repair. Do not cover cord with throw rugs, runners, or the like. Arrange cord away from traffic area and where it will not be tripped over. Do not use on soft surfaces, like a bed, where openings may become blocked. Do not use in areas where gasoline, paint, or flammable liquids are used or stored or where the unit will be exposed to flammable vapors. Use it only as described in this manual. Any other use not recommended by the manufacturer may cause fire, electric shock or injury to persons. Extension cords may overheat and cause a risk of fire. If you must use an extension cord, the cord shall be No. 16 AWG minimum size and rated not less then 1875 watts.

https://ayurvedia.ch/boss-br-900cd-user-manual

Ensure that all three of the inserts feet rest securely on this surface. Do not install into an existing fireplace that is prone to dampness. Apply Today! Data is protected for your safety. Subject to approval and standard underwriting criteria. Please see afirst.loan for details. Because American First Finance AFF services FinWise Bank installment loans, please contact AFF regarding any questions about FinWise Bank installment loans. American First Finance FAQ 1. What is "No Credit Needed" or "Regardless of Credit". Your credit may be checked, including your credit score, but the

application process does not solely depend on your credit score for an approval. 2. What are the requirements to qualify for the Regardless of Credit solution. A typical credit check, also known as a credit history check, is when a company views your history of credit, other accounts, and credit score with a credit reporting agency, also known as a credit bureau. 4. Do you perform credit checks. When you apply for a financial solution through American First Finance, your credit is checked using a hard credit inquiry also known as a "hard credit pull". A hard inquiry occurs when a company with whom you've applied for credit reviews your credit report, history of applying for credit, payment history, and your credit score as part of the decisionmaking process. This type of inquiry appears on your credit report and may influence your credit score. Applicants with mediocre, poor, or even no credit can still receive an approval, but a credit check is part of the application process. You are invited to apply no matter what your credit history is! 5. What if I have bad credit or filed for bankruptcy in the past. You can still get approved. An ITIN is an Individual Tax Identification Number issued by the federal government for noncitizens working and paying taxes in the U.S. 7. Do I need to have a job to apply.

http://jms-stavebni.com/images/Dialysis-Technology-A-Manual-For-Dialysis-Technicians.pdf

Fulltime employment is not necessary as we may consider different forms of income, such as income from Social Security, retirement, pension, and selfemployment. 8. What is an ACH authorization. An ACH Authorization is your verbal or written instructions that allow us to electronically withdraw a specified amount of money from a bank account or debit card on an agreedupon day. 9. How do I make my payments. If you have selected to have your payments automatically reoccurring, payments will be ACH transferred from the bank account or debit card provided on your application. If you have not selected to have your payments automatically reoccurring, you can access your account via www.americanfirstfinance.com to make your required payment. Charges will appear on your statement as American First Finance, not the store where you selected your merchandise. 10. How do I know when a payment's due. The first payment and schedule of payments are provided in the loan documents. It is also provided after the application is completed. Additionally, you can see your payment schedule online in your customer account at www.americanfirstfinance.com. 11. Can I cancel this loan. Yes, just be sure to cancel before you make a transaction with your virtual card. 12. Who is American First Finance. American First Finance is a leading consumer financial technology company that provides alternatives to traditional retail lending and designs solutions to support both businesses and their financially underserved or overlooked customers. American First Finance services FinWise Bank installment loans. 13. Who is FinWise Bank. FinWise Bank, member FDIC, is located in Murray, Utah, and is the lender for all American First Finance installment loans. Virtual Card FAQs 1. What is a limiteduse virtual card. A virtual card is a digital version of a physical, plastic credit card. It is a set of sixteen digits similar to a credit card number together with a CVV code that is used for payment transactions.

https://koeltotaal.com/images/Dialysis-Technician-Training-Manual.pdf

This card will be displayed on your smartphone or laptop screen upon completion of your loan documents and can be used immediately for purchases. 2. What are the benefits of a virtual card. A virtual card will instantly appear in your app and can be used right away so you can securely pay for goods online and over the phone, without displaying any of your personal or financial information or waiting for a plastic card to arrive in the mail. And, since it's a virtual card, it is less likely to be lost or stolen. 3. When will the funds be uploaded to my virtual card. Funds will be available through your virtual card upon the completion of your loan documents. 4. How can I access my virtual card, or what if I have not received my virtual card. The virtual card will initially be displayed upon completion of your loan documents. If you have used your virtual card, it will no longer be displayed, and any unused funds will be ACH transferred to your bank account. 5. Where can I use my virtual card. Your virtual card can be used online or over the phone for any purchase. If you plan on using

your virtual card in a store, simply show the cashier your virtual card and they can enter the card information manually in a "card not present" transaction. Please note, acceptance of a "card, not present" transaction is up to the merchant or store's discretion. 6. What is a pending transaction. A pending transaction is a payment which has been authorized, but it's still waiting for the merchant to accept or reverse it. The merchant has up to seven days to do this, but it can take up to 15 days if it's an ecommerce preauthorization. The money will be sent back to your card automatically if the merchant hasn't taken any actions after this timeframe. Virtual cards should not be used for recurring card payments e.g., subscriptions or monthly payments or with merchants requiring a preauthorization e.g., car rentals or hotel bookings. 7. What happens to my unused funds.

If you use any amount of your virtual card, the remaining funds will be ACH transferred to your bank account that you provided during the application process, once your pending transactions have finalized. If you have NOT used any portion of the funds on your virtual card, those funds will be ACH transferred to your bank account after four days from signing your loan documents. 8. What if my payment is due and I haven't used my virtual card or received the funds yet. American First Finance will not collect payment if you have not initiated a transaction with your virtual card. The initial transaction will trigger an update to your payment due date and will align with your pay cycle frequency indicated on your application. If you have not used your funds in four days, funds will be ACH transferred to your account, and the date those funds are transferred will trigger an update to your payment due date and will align with your pay cycle frequency indicated on your application. Have Additional Questions. Give us a call or drop us an email, we're here to help seven days a week. Suggestions Use a search term in the search box above. Click on a category link above to browse. Visit our homepage. WERE HERE TO HELP Contact Us Customer Service Hours 18887681710 MondayFriday 800am 600pm CST Sales Hours MondayFriday 800am 800pm CST Saturday and Sunday 930am 530pm CST St. Louis Store Showroom Hours MondayFriday 1100am 500pm CST ABOUT US Investor Relations Customer Reviews POLICIES Complete Policies Privacy Policy CCPA Policy Coronavirus Deliveries St. Get special offers, learn about new rebates, and receive home improvement tips right in your inbox. Newsletter Email address not valid Invalid Request Please refresh page and try again. There are two types of electric fireplace inserts fireboxes and logs. Here we will cover the installation of firebox inserts into the existing fireplaces.

However, in most cases, you will need to hire a licensed electrician to help you install a power outlet inside your old fireplace opening. Please note that they may be slightly different depending on a particular brand of the electric insert you are installing. Please refer to the product manual of your electric insert for details. This cover plate will prevent water from coming in if your chimney doesnt have a rain cap. If you want to keep the area around your fireplace free of hanging cords, you will need to install an outlet inside of your existing fireplace. Then center, and level it. You might need to adjust the leveling screws if those are available with your model of the electric insert. Some inserts will have tiedown brackets that you will need to attach to the fireplace floor and the back of the insert on both sides to secure your insert from tipping. Some inserts come with glass frames, others with metal trim. You can also use your own custom trim like in the video. The installation might be slightly different depending on the brand and your particular project. Most of the product manuals are published on our website in downloadable PDF format on each product page. Installation is a simple twostep process Preparation and Installation. Here is how its done. This begins the curing process. Until the steel gets heated up and cured there will be some runoff. Each time the fire pit is used the patina bakes into the steel and less runoff occurs. In this article, you will find videos with step by step instructions and a downloadable PDF installation manuals to help you properly install and use your new water vapor fireplace. Page Count 15 Over the year s, valuable memories will o ccur around t he warmth and comfort of yo ur hearth. Tha nk you for allowing our product to be the backdrop for t hose special moments. Quality checke d by 7203810100 REV08 This odor is a normal condition caused by the initial heating of internal heater parts and will not occur again.

3 If your heater does not emit heat, ensure the switch is on and the thermostat is turned fully to the right. If this does not work, switch the unit off for 5 minutes and try again. Consult page 5 of your Practical Users Guide for furthe r information. The trim around the heater out let becom es hot d uring h eater operation. Return heater to author ized s ervice facility for exam ination, electrical or mec hanical adjus tm ent, or repair. 10. Do not use outdoors. 11. Do not use t his firep lace in the imm ediate surroun dings of a bath, a sho wer or a swimm ing pool. 12. Do not instal I the firep lace directly on carpet or a similar surface which may restrict air circulation beneath the unit. 13. Do not run t he cord un der c arpeting. Do not co ver cord with throw r ugs, runners, or the like. Arrang e cord away from traffic area and w here it will not be trip ped over. 14. Do not locate the heat er im mediatel y below a fixed s ock etoutlet. 15. To disconnec t the firep lace, turn the contr ols off, then rem ove the plug f rom the outlet. 16. Do not insert or allo w foreign objects to enter an y ventilation or exhaus topening as this may cause an electric shock or fire, or damage to the heat er. 17. To prevent a p ossible f ire, do n ot block air intak e or exhaust in any m anner. Do n ot use on soft surfaces, like a bed, where openings may become blocked. 18. All electrical heaters h ave hot an d arching or spark ing parts inside. D o not us e in areas where gas oline, paint, or flam mable liquids are us ed or stor ed or where the unit will be exposed to flamm able vapors. 19. Do not m odif y the electr ic fireplace. U se it only as desc ribed in th is m anual. Any other use not rec omm ended by the m anufacturer may cause fire, e lectric shock or injury to pers ons. 20. Avoid the us e of an ex tension c ord. Extens ion cor ds ma y overheat an d cause a risk of fire.

If you must us e an extensio n cord, the c ord shall be No. 16 AW G minim um size and rat ed not les s then 1875 watts. 21. Do not burn wood or other m aterials in the electric f ireplace. 22. Do not strik e the firep lace glass. 23. Always us e a certif ied electr ician should n ew circu its or outl ets be requ ired. 24. Always us e properl y grounded, f used and polarize d outlets. 25. Disconnect all po wer supply before performing any cleaning, maintenance or relocation of the unit. 26. When transporting or st oring the unit and c ord, k eep in a dr y place, free f rom excessive vibration and s tore so as to avo id dam age. NOT E Procedures and te chniques that are considered important enough to emphasize. CAUTION Procedures and techniques which, if not car efully followed, w ill result in damag e to the equipment. WARNING Procedur es and techniques w hich, if n ot carefull y follow ed, will expose the use r to the risk of fire, serious injury, illn ess or de ath. Existing F ireplace. New W all Constructio n.E nsure that a ll three of the i nserts f eet rest sec urel v on this surf ace. Existing F ireplace 1. Seal all drafts and vents with no nfiberous insulation materials to prevent ch im ney debris from falling onto the Fireplac e Insert. A dedicat ed circ uit is preferr ed but not es sential in all cas es. A dedic ated circuit wil l be required if, after installation, the circ uit breaker trips or fus e blows on a re gular bas is when t he heater is op erating. A dditional app liances on the same circuit may exceed the current rating of the circuit breaker. To prevent elec trical shock this unit is a n electrical appliance that is not watertight and must be installed as to prevent water from entering unit. This mu st be installed away from showers, tubs, etc. Never loca te fireplace where it ma y fall into a bathtub o r other water conta iner.

Keep towels a nd other combustib le materials 3 feet a way from the front of the unit. 3A If the cord does n ot reach you may use an ex tension cor d rated for a m inim um of 1875 W ATTS. 4. Push the F ireplace into place e so that the trim is against the finished Mantel S urround or wall sur face. FIGURE 6. 5. Level, if requ ired with wood s hims not included FIGURE7. 4 FIREPL ACE INSERT INST ALLA TIO N PUSH FIGURE6 TRIM W ALL OR MANTEL INSERT It does this by turning the heater on and off. The heater is protected with a safety device to prevent overheating. Should the heater overheat, an automatic cut out will turn the heater of f and it will not come back on without being reset. Leave in this position to maintain the room temperature at its setting. For additional heat, turn clock wise until you hear the click again and the heater will turn on. To lurn the heater off, rotate the knob full y counter clock wise. Light bulbs need to be replaced when you notice a dark section of the flame or when the clarity and detail of the log exterior disappears. T

here are two b ulbs at t he top of the openin g which illuminate the log set exterior, and four bulbs under the log set which generate the f lames and ember s. Too l Requirements Slot Scre w Driver FIGURE10a,b,c REMOVINGGLASS REPLACINGGLASS a b c HOLDINGGLASS RET AININGCLIP M A INTEN A NCE P ull out until the rear tab c lears the b ack ledge, then l ift out. FIGUR E 12 2. Exam ine the bulbs to determ ine which bul bs require replacement. 3. Hold the soc ket while unscre wing the bulb. FIGURE 13 4. Hold the soc ket while screwing in the new bulb. 5. Replace the log by pushing it down and in until it rests against the mirror. FIGURE 12 GLASS COUCH Anexampleofasafestorageplace FIGURE1 1 FIGURE12 LIFTINGOUT LOG EMBERBED SIDESECTION LOG EMBERBED BACKLEDGE REAR TAB FIGURE 13 During shipment, installation, handlin g, etc.

, the glass surface may collect dust particles; these can be removed by buffing lightly with a clean dry cloth. To rem ove finger prints or other marks, the glass can be cleaned with a dam p cloth us ing a good qualit y household g lass clea ner. The g lass shou ld be com pletel y dried with a lint free c loth or pap er towel. Helpful Hints W ait until it is tim e to change the light bulbs to clean inside glass surface. FIGURE14 This limited warranty applies to the original purchase r of the product only and is not transferable. Products purcha sed in Yukon Territo ry, Nunavut, Northwest T erritories, Hawaii, or Alaska are not covered by this lim ited warranty. Products purch ased in these State s, provinces, or territories a re sold AS IS withou t warranty or con dition of any kind includ ing, without limitation, any implied warranties or conditions of merchantability or fitness for a pa rticular purpose and the entire risk of a s to the quality and pe rformance of the product s is with the purchase r, and in the event of a def ect the purchase r assumes the entire cost of all necessary servicing or repa ir. What this limited warranty covers and fo r how long Products, o ther than fireplace surrou nds mantels andd trims, covered by this limited warranty have been tested and inspected prior to shipme nt and, subject to the p rovisions of this warranty, Dimplex warrants suc h products to be free from defects in material and workman ship for a period of 2 years from the date of the first p urchase of such product s. Dimplex f ireplace surrounds mantels and trims covered by this limited warranty have been tested and inspected prior to shipmen t and, subject to the provisions of this warranty, Dimple x warrants such products to be free from defect s in material and workman ship for a period of 1 year from the date of f irst purchase of such products.

The limited 2 year warranty period for products other th an fireplace surround s mantels and trims and the limited 1 year warranty period for fireplace surround s mantels and trims a lso applies to any implied warranties that may exist under applicable law. Some jurisdictions do not allow limitation s on how long an implie d warranty lasts, so the above limitation may not apply to the purchaser. What this limited warranty does not cove r This limited warranty do es not apply to products that have be en repaired except by Dimplex or its authorized service rep resentatives or ot herwise altered. This lim ited warranty does further n ot apply to defe cts resulting from misus e, abuse, accident, neglect, incorrect installation, improper maintenance or handling, or operation with an incorrect power source. 9 Limited warranty service requires a proof of purchase of the product. The purchaser is responsible for removal and transportation of the surrounds man tels and trims and any repaired or rep lacement product or part to and from the authorized dealers or service agents place of business. On site or in home se rvices for surrounds mante ls and trims may be performed at the purchasers specific request and expense at Dimp lexs then current rate s for such services. Dimp lex will not be responsible for, and this limited warranty shall not include, any expense in curred for installation or remo val of the surrounds mante ls or trims or any part thereof or any replacem ent product or part includin g, without limitation, all shipping costs and t ransportation costs to and from the authorized de alers or service agents place of business and all lab our costs. Such co sts shall be the purch asers responsibility. 10 The provisions of the United Nations Convention on Contracts for the Sale of Goods shall not apply to this limited warranty or the sale of products covered by this limited warrant y.

Approved for use in the United States and Canada Printed in Ch ina 1 88 8 DI MP LE X 18 8 8346 753 9 1367 Industria l Road Cam bridge, Ontario Canada, N1R 7G 8 11. You can fit the logs easily in an existing fireplace without having to worry about fuel. The fact that electricity is cheap and available everywhere gives these logs an edge the most preferred heat source. When looking to upgrade your fireplace, electric logs are the direction to take. Different brands are flooding the market, and sometimes selecting the best electric fireplace logs can be challenging. Below, we have reviewed some of those worthy options, led by Duraflame DFI021ARU and Dimplex Revillusion RLG25, that you can count on your fireplace without thinking twice. This set of logs is placed in an existing fireplace and produces an undeniably realistic flame. The flame is projected to the rear, giving it an authentic look. You can operate the flame with or without heat for decoration purposes. These infrared guartz logs are neatly arranged and sit on a black fire grate and resemble a real Oak. The pulsating dancing flame will impress you with the look of real Oak wood fire. As it uses infrared technology, it efficiently distributes the heat in the room. It also helps in maintaining comfortable air humidity in your house. You can control the logs from your seat anywhere via the remote control included in the package. The handheld remote has functions for turning on and off, adjusting the heat output, and controlling the flames effect. How do you install the fireplace. Installation of the unit is easy since no venting or fuel lines are required. Just place the grate in the fireplace, pass the cord to the back of the fireplace, connect to a power supply, and you are good to go. With these logs, you can enjoy a favorable temperature in your house despite outdoor changes. Dimplex Log Set insert comes with a ceramic burner with a capacity of up to 5,000 BTU.

https://congviendisan.vn/vi/boss-br-900cd-user-manual